

BOA-SKI

November 12, 1970

TO: ALL BOA-SKI SNOWMOBILE DEALERS!

CUSTOMER SERVICE INFORMATION

BULLETIN NO. 21

Gentlemen:

We are pleased to advise that a modified wiring harness is now available for machines using the 340 cc. C.C.W. Recoil Start Engine.

The procedure to install this harness is, as follows:

- Step No. 1 Remove hood from machine and disconnect hood harness and single pole single throw switch.
- Step No. 2 Install new single pole double throw switch (attached to new harness) in a horizontal position in hood. Do not disconnect any terminals from this switch. Connect five prong female plug to terminals on ignition switch.
- Step No. 3 The two terminals, each containing a double blue wire, should be connected to the two terminals on the right hand headlamp. Check to ensure that the correct sealed beams (No. 4415-1) are installed in hood.
- Step No. 4 Connect the terminal containing a double brown wire to one side of the resistor, and the terminal containing a single brown wire to the other resistor terminal.
- Step No. 5 The single blue and brown wires taped together should be connected to the left hand sealed beam, one wire to each terminal.
- Step No. 6 The single blue wire with no terminal should be connected to the speedometer.
- Step No. 7 Install hood on machine and connect the six prong plug into the engine harness.

- continued -



Customer Service Information
Bulletin No. 21

-2-

Please ensure that the wiring is arranged in such a way that undue tension is avoided, eliminating the possibility of the wiring working loose.

Yours very truly,

F. MANLEY & SONS LIMITED

B. R. Upton.

B. R. Upton,
Manager,
Customer Service Department.